





# noraplan®

Test	Product	degree	eco	environcare™	sentica	environcare™ acoustic/ sentica acoustic	environcare™ ed/ sentica ed	unita
Limited Wear Warranty in years		5	5	5	5	5	5	5
10-year nora® pro install system warranty*		Yes	Yes	Yes	Yes	Yes	Yes	Yes
Taber Abrasion ASTM D3389 H-18 Wheel (1000 cycles) 500 gram load—grams weight loss		< .4	< .4	< .4	< .4	< .4	< .4	< .4
Shore Hardness "A" ASTM D2240		≥ 85	≥ 85	≥ 85	≥ 85	≥ 85	≥ 85	≥ 85
Rolling Load Limit/PSI (2) (Forklift Traffic)		550 (no)	450 (no)	2.0 mm–450 3.0 mm–550 (no)	2.0 mm–450 3.0 mm–550 (no)	450 (no)	450 (no)	450 (no)
Static Load Limit 800 Lbs./Sq. In. ASTM F970 Residual Compression		≤ .005"	≤ .005"	≤ .005"	≤ .005"	≤ .005"	≤ .005"	≤ .005"
Static Coefficient of Friction ASTM D2047								
Critical Radiant Flux ASTM E648 (not less than .45 W/per cm²)		Class 1	Class 1	Class 1	Class 1	Class 1	Class 1	Class 1
NBS SMOKE DENSITY ASTM E662		< 450	< 450	< 450	< 450	< 450	< 450	< 450
Cigarette burn and solder resistance								
Halogen-free								
Resistance to: acids—alkalies—solvents—other chemicals (1)								
Oil and grease resistance		No	No	No	No	No	Yes	No
Static Generation Comparison Less than 10 Volts per ESD STM 97.2**		—	—	—	—	—	< 20	—
ESD-S7.1/ASTM F150 RH > 30% at room temperature 10 Year Limited Conductivity Warranty (ohms)		—	—	—	—	—	10 <sup>6</sup> < 10 <sup>9</sup>	—
Decay-time FTM 101 C 4046 (sec.)		—	—	—	—	—	< 25	—
GREENGUARD Indoor Air Quality Certified®		Yes	Yes	Yes	Yes	Yes	Yes	Yes
GREENGUARD Children and Schools™ Certified		Yes	Yes	Yes	Yes	Yes	Yes	Yes
CA 01350 Compliant		Yes	Yes	Yes	Yes	Yes	Yes	Yes

(1) Call nora systems, Inc. for details.

(2) No metal or hard plastic wheels, the shape of contact surfaces of equipment wheels must be flat, and the wheels shall be ≤ 90 shore hardness type A.

\*Registration for 10-year nora pro install system warranty required.

\*\*Tested with conductive shoes.

**nora systems, Inc.**

9 Northeastern Blvd.  
Salem, NH 03079  
Toll free: 800-332-NORA  
Phone: (603) 894-1021  
Fax: (603) 894-6615  
E-mail: info-us@nora.com  
www.nora.com/us



All About Flooring. All About You.