



nora[®] pro clean pads 1, 2 and 3

Product Description:

These are floor maintenance pads made of polyester fiber in a non-woven web with resins throughout, which are bonded to the structure. One side of the pad is prepared with diamond powder, fixed with adhesive. The pads are normally approximately one inch thick, and available in a variety of sizes.

Intended Use:

This pad was developed to be used for cleaning, polishing and daily maintenance of specific nora[®] rubber floor coverings only (not for use with norament[®] luxor or round pastille surfaces). Always follow the nora[®] pro clean maintenance guide that is available on www.nora.com/us. These are intended for use with a suitable cleaning machine by maintenance professionals.

1. Packaging: Four pads per box (brown)
2. Standard sizes: 13, 14, 17 and 20 inch (others may be available upon request)
3. Thickness: ASTM D5736, 1 inch \pm 0.16 inch (25mm \pm 4mm)
4. Weight: ASTM D6242, 2.1 lbs (956g) – 2.6 lbs/m² (1185g)
5. Center hole: Pre-cut at 3 1/4 inch (82.6mm)
6. Composition: Polyester non-woven fiber pad
7. Impregnation: Phenolic plastic, hardener and diamond fillers
8. Recycled content: \geq 15% post consumer recycled material
9. Average tensile strength: ASTM D461, 65 psi
10. Warranty: As detailed in the nora Warranty
11. Coverage pad 1: Approximately 100,000 square feet
12. Coverage pad 2: Approximately 80,000 square feet
13. Coverage pad 3: Approximately 40,000 – 60,000 square feet
14. Machine speed: Cleaning 150 – 400 rpm, Buffing ~1800 (without suction skirt)
15. Wet Cleaning: After 72 hours

General Remarks:

nora floor coverings have a production residue. This residue shall be removed (initial maintenance) before the flooring is used, otherwise it will attract dust and dirt. nora floor coverings have a natural sheen, therefore they do not require any artificial coating. For area specific maintenance guides, visit www.nora.com/us or contact the Technical Department.

General Precautions:

- Always use “wet floor” signs and/or caution tape when performing any wet cleaning.
- Refer to MSDS for proper personal protection requirements before using cleaning products.
Note: the printed side of the pad goes to the machine and the non-printed side of the pad goes to the floor.
- When using nora pads, do not scrub the floor dry. Rubber flooring must be kept “wet” with clean water or solution.
- The floor will be slippery when wet or contaminated with foreign materials. To maintain the slip resistant properties of the flooring, promptly clean-up spills and any foreign materials.
- Never use black or brown stripping pads or brushes.
- Make sure to maintain a good walk-off area in the entrance of the facility, in addition to regular dust mopping.
- Spots from petroleum-based products such as grease and tar must be removed with spotting agents containing solvents. Immediately rinse with water after spot removing and allow time to dry.
- Remove chewing gum with a gum removing spotter. If a solvent is used for removing gum, immediately rinse the floor with clean water and allow time to dry.
- Do not allow any metal furniture or trash cans to be in contact with the wet floor.

Initial Maintenance:

A general cleaning shall be performed a minimum of 72 hours after installation. The following procedures shall be performed by the facility prior to the floor being opened to general traffic.

1. Dust mop or vacuum the floor to remove dirt or grit.
2. Remove any adhesive residue.
3. Survey the floor for any areas with construction damage.
4. Wet mop an area using green seal certified cleaner.
5. Scrub the floor thoroughly with a floor scrubber using nora pad 1 (see note for areas with construction damage). Do not allow the area to dry during scrubbing.
6. Wet vacuum the soiled solution, rinse the floor with clean water and allow to dry.

Note: Areas with Construction Damage: Scrub first with nora pad 3, pick up residue with wet vacuum and continue from Step 4 above.

For High Shine: Damp mop the floor and while floor is damp, burnish to a shine with nora pad 1 (do not use burnisher with a speed higher than 1,800 rpm).

Daily Maintenance:

1. Dust mop or vacuum the floor to remove dust and dirt.
2. Auto-scrub the floor using nora pad 1 with clean water.
3. Wet vacuum the soiled solution and allow time to dry.

Periodic Maintenance:

1. Dust mop or vacuum the floor to remove dust and dirt.
2. If required, remove any chewing gum with a gum removing spotter. If a solvent is used for removing gum, immediately rinse the floor with clean water.
3. Auto-scrub the floor with nora pad 2 using clean water. Continue using nora pad 2 until all dirt residue is removed.
4. Once all surfaces are clean, repeat cleaning process with nora pad 1.
5. Wet vacuum the soiled solution, rinse the floor with clean water and allow time to dry.

Note: To increase the shine, the floor can be dry-buffed using a 3M™ #4100 white pad or wet burnish with nora pad 1.

Maintenance of Pad:

1. Remove pad from machine after each use.
2. Clean your pads thoroughly by rinsing with clean water and allowing to dry.

Precautions:

Keep out of reach of children. Use of protective gloves (rubber) and safety glasses is recommended.

First Aid:

In case of skin contact, wash thoroughly with soap and water. If swallowed, obtain medical help immediately.

Disposal:

Disposal should be in accordance with local, state and federal regulation. Empty packaging can be recycled.

For more information, please refer to the MSDS that must be read and fully understood prior to using the nora pro clean system. The MSDS and specific maintenance guides are available on www.nora.com/us.

Dated: August 2011

nora systems, Inc.

9 Northeastern Blvd.
Salem, NH 03079
Toll free: 800-332-NORA
Phone: (603) 894-1021
Fax: (603) 894-6615
E-mail: info-us@nora.com
www.nora.com/us