



# nora<sup>®</sup> stair accessories

## Product Description:

A rubber floor covering manufactured by nora systems, Inc. that is approved by Lloyd's Register Quality Assurance to the Quality Assurance Management System Standard ISO 9001:2000. Also ISO 14001 Environmental Management Systems certified.

## Rubber stair accessories

1. Product Name: nora<sup>®</sup> T5044 A/C stair nosing, Article 802, for flooring 0.8 inches (2mm) to 0.11 inches (2.7mm)  
nora<sup>®</sup> T5044 E/F stair nosing, Article 802, for flooring 0.14 inches (3.5mm) to 0.16 inches (4mm)  
nora<sup>®</sup> T 5049 A/C stair nosing, Article 805, for flooring 0.8 inches (2mm) to 0.11 inches (2.7mm)  
nora<sup>®</sup> T 5049 E/F stair nosing, Article 805, for flooring 0.14 inches (3.5mm) to 0.16 inches (4mm)
2. Material: nora rubber compound 961 with abundant natural fillers and environmentally compatible color pigments
3. Color: As selected
4. Nosing Back: Smooth, double-sanded back
5. Composition: Homogeneous rubber compound 961
6. Limited Wear Warranty: 5 years
7. Static Load: Per ASTM F970 Standard Test Method for Static Load Limit, residual compression, when tested with 800 lbs.  $\leq$  0.005"
8. ISO 14001: Manufacturer shall be ISO 14001 Environmental Management Systems Certified
9. PVC Free: Product shall contain no polyvinyl chloride
10. Abrasion Resistance: Taber abrasion test, ASTM D3389, H-18 wheel, 500 gram load, 1000 cycles, gram weight loss,  $\leq$  0.4
11. Slip Resistance: Static coefficient of friction (James Test), ASTM D2047,  $\geq$  0.8
12. Bacteria Resistance: Product shall be resistant to bacteria, fungi, and micro-organism activity, according to ASTM E2180 and ASTM G21
13. Halogen Free: Product shall contain no halogens
14. Burn Resistance: Cigarette and solder burn resistance
15. Flammability: ASTM E648; NFPA 253; NBSIR 75 950,  $\geq$  0.45 watts per square centimeter, Class 1
16. Smoke Density: ASTM E662, NFPA 258, NBS smoke density,  $<$  450
17. Asbestos Free: Product shall contain no asbestos
18. Non Hazardous: Nosings shall be made without any chemicals that may be hazardous or containing any teratogenic, mutagenic or any other ingredients known to be carcinogenic
19. Cleaning: Nosing surface shall have the ability to be cleaned and maintained without the use of any chemicals that may be hazardous or containing any teratogenic, mutagenic or any other ingredients known to be carcinogenic. Flooring shall be cleanable using Green Seal certified products, without the use of factory and/or field-applied coatings
20. Installation System: Use only nora<sup>®</sup> pro install system products following the current nora Installation Guide that may consist of part or all of the following steps depending upon the substrate conditions and requirements of the specific project.
  - Step 1 – nora<sup>®</sup> membrane (see Installation Guide for requirements).
  - Step 2 – nora<sup>®</sup> primer (see Installation Guide for requirements).
  - Step 3 – nora<sup>®</sup> leveler (see Installation Guide for requirements).
  - Step 4 – nora<sup>®</sup> patch (see Installation Guide for requirements).
  - Step 5 – nora<sup>®</sup> adhesives, the flooring usage and substrate conditions will determine the appropriate adhesive. Contact your nora representative for specific recommendations.

For more information, please refer to the MSDS, Installation Guides and Guide Specifications available on [www.nora.com/us](http://www.nora.com/us).

## Rubber stair accessories

1. Product Name: nora® banister trim, Article 744 (A 5013 U)
2. Material: nora rubber compound 959 ASTM F1861 Type TP - rubber, thermoplastic. With abundant natural fillers and environmentally compatible color pigments
3. Color: As selected
4. Trim Size: 8.2 foot (2.5m) length
5. Limited Wear Warranty: 5 years
6. Composition: Homogeneous rubber compound 959
7. ISO 14001: Manufacturer shall be ISO 14001 Environmental Management Systems Certified
8. PVC Free: Product shall contain no polyvinyl chloride
9. Halogen Free: Product shall contain no halogens
10. Flammability: ASTM E648; NFPA 253; NBSIR 75 950,  $\geq 0.45$  watts per square centimeter, Class 1
11. Smoke Density: ASTM E662, NFPA 258, NBS smoke density,  $< 450$
12. Non Hazardous: Trim shall be made without any chemicals that may be hazardous or containing any teratogenic, mutagenic or any other ingredients known to be carcinogenic
13. Installation System: Use only nora® pro install system products following the current nora Installation Guide that may consist of part or all of the following steps depending upon the substrate conditions and requirements of the specific project.
  - Step 1 – nora® membrane (see Installation Guide for requirements).
  - Step 2 – nora® primer (see Installation Guide for requirements).
  - Step 3 – nora® leveler (see Installation Guide for requirements).
  - Step 4 – nora® patch (see Installation Guide for requirements).
  - Step 5 – nora® adhesives, the flooring usage and substrate conditions will determine the appropriate adhesive. Contact your nora representative for specific recommendations.

For more information, please refer to the MSDS, Installation Guides and Guide Specifications available on [www.nora.com/us](http://www.nora.com/us).

Dated: March 2012

### **nora systems, Inc.**

9 Northeastern Blvd.  
Salem, NH 03079  
Toll free: 800-332-NORA  
Phone: (603) 894-1021  
Fax: (603) 894-6615  
E-mail: [info-us@nora.com](mailto:info-us@nora.com)  
[www.nora.com/us](http://www.nora.com/us)