



nora[®] base accessories

Product Description:

A rubber floor covering manufactured by nora systems, Inc. that is approved by Lloyd's Register Quality Assurance to the Quality Assurance Management System Standard ISO 9001:2000. Also ISO 14001 Environmental Management Systems certified.

Resilient wall base / sanitary base / accessories

1. Product Name: nora[®] wall base (S 1028 B), Article 820
 2. Material: nora rubber compound 999, ASTM F1861, Type TP - rubber, thermoplastic. With abundant natural fillers and environmentally compatible color pigments
 3. Color: As selected
 4. Size: 0.125 inches (3.175mm) thick, 4 inches (102mm) high, 120 feet (36.5m) rolls
 5. Composition: Homogeneous rubber compound 999
 6. Limited Wear Warranty: 5 years
 7. ISO 14001: Manufacturer shall be ISO 14001 Environmental Management Systems Certified
 8. Halogen-Free: Product shall contain no halogens
 9. Installation System: Use only nora[®] pro install system products following the current nora Installation Guide that may consist of part or all of the following steps depending upon the substrate conditions and requirements of the specific project.
 - Step 1 – nora[®] membrane (see Installation Guide for requirements).
 - Step 2 – nora[®] primer (see Installation Guide for requirements).
 - Step 3 – nora[®] leveler (see Installation Guide for requirements).
 - Step 4 – nora[®] patch (see Installation Guide for requirements).
 - Step 5 – nora[®] adhesives, the flooring usage and substrate conditions will determine the appropriate adhesive. Contact your nora[®] representative for specific recommendations.
-
1. Product Name: nora[®] sanitary wall base, Article 817 (S 3019 D)
 2. Material: nora rubber compound 959, ASTM F 1861, Type TP - rubber, thermoplastic. With abundant natural fillers and environmentally compatible color pigments
 3. Color: As selected
 4. Size: Top leg 0.12 Inches (3mm) thick, 5.98 inches (152mm) high; connection dimension bottom leg 0.13 inches (3.2mm) thick, 2.0 inches (50mm) long. Available in 32.8 foot (10m) length
 5. Composition: Homogeneous rubber compound 959
 6. Limited Wear Warranty: 5 years
 7. ISO 14001: Manufacturer shall be ISO 14001 Environmental Management Systems Certified
 8. PVC Free: Product shall contain no polyvinyl chloride
 9. Halogen Free: Product shall contain no halogens
 10. Flammability: ASTM E648; NFPA 253; NBSIR 75 950, ≥ 0.45 watts per square centimeter, Class 1
 11. Smoke Density: ASTM E662, NFPA 258, NBS smoke density, < 450
 12. Non Hazardous: Base shall be made without any chemicals that may be hazardous or containing any teratogenic, mutagenic or any other ingredients known to be carcinogenic.
 13. Installation System: Use only nora[®] pro install system products following the current nora Installation Guide that may consist of part or all of the following steps depending upon the substrate conditions and requirements of the specific project.
 - Step 1 – nora[®] membrane (see Installation Guide for requirements).
 - Step 2 – nora[®] primer (see Installation Guide for requirements).
 - Step 3 – nora[®] leveler (see Installation Guide for requirements).

Step 4 – nora® patch (see Installation Guide for requirements).

Step 5 – nora® adhesives, the flooring usage and substrate conditions will determine the appropriate adhesive. Contact your nora® representative for specific recommendations.

1. Product Name: nora® cove stick, Article 7731
2. Material: nora rubber compound 959, ASTM F 1861 Type TP - rubber, thermoplastic. With abundant natural fillers and environmentally compatible color pigments
3. Size: 32.8 foot (10m) length
4. Composition: Homogeneous rubber compound 959
5. Limited Wear Warranty: 5 years
6. ISO 14001: Manufacturer shall be ISO 14001 Environmental Management Systems Certified
7. PVC Free: Product shall contain no polyvinyl chloride
8. Halogen Free: Product shall contain no halogens
9. Non Hazardous: Cove shall be made without any chemicals that may be hazardous or containing any teratogenic, mutagenic or any other ingredients known to be carcinogenic
10. Installation System: Use only nora® pro install system products following the current nora Installation Guide that may consist of part or all of the following steps depending upon the substrate conditions and requirements of the specific project.
 - Step 1 – nora® membrane (see Installation Guide for requirements).
 - Step 2 – nora® primer (see Installation Guide for requirements).
 - Step 3 – nora® leveler (see Installation Guide for requirements).
 - Step 4 – nora® patch (see Installation Guide for requirements).
 - Step 5 – nora® adhesives, the flooring usage and substrate conditions will determine the appropriate adhesive. Contact your nora® representative for specific recommendations

For more information, please refer to the MSDS, Installation Guides and Guide Specifications available on www.nora.com/us.

Dated: March 2012

nora systems, Inc.

9 Northeastern Blvd.

Salem, NH 03079

Toll free: 800-332-NORA

Phone: (603) 894-1021

Fax: (603) 894-6615

E-mail: info-us@nora.com

www.nora.com/us