

# nora<sup>®</sup> ED 120

Fiber-reinforced conductive acrylic adhesive

nora<sup>®</sup> ED 120 is an easy-to-use, fiber-reinforced, wet set, conductive, water based acrylic adhesive that has been specifically formulated for the installation of specific nora<sup>®</sup> ED rubber floor coverings (2 mm - 4 mm) on absorptive substrates. Also part of the nora one<sup>®</sup> system solution.

- Excellent for heavy traffic
- Non-flammable and freeze/thaw stable
- Free of organic solvents, formaldehyde, asbestos, lindane, rosins, plasticizers or any other volatile components
- Meets the South Coast (CA) Air Quality Management District Rule 1168
- Meets VOC emissions and content requirements of LEED, including REACH

## nora ED 120 – Art. 6695

Shelf Life	12 Months
Application	1/16" x 1/16" x 1/16" square-notch trowel
Coverage	~480 - 540 square feet per 3 gallon pail
Open Time	5 -15 Minutes
Working Time	25 Minutes
Storage	Room temperature and away from direct sunlight
Moisture Limit	≤ 85% RH following ASTM F2170 <i>Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using in situ Probes</i>
Freeze/Thaw stable	Stable per ASTM D7149 at 0°F (-18°C)

For information on the nora one<sup>®</sup> system solution visit [www.nora.com/us/noraone](http://www.nora.com/us/noraone)

### nora systems, Inc.

9 Northeastern Blvd.  
Salem, NH 03079  
Toll free: 800-332-NORA  
Phone: (603) 894-1021  
Fax: (603) 894-6615  
E-mail: [info-us@nora.com](mailto:info-us@nora.com)  
[www.nora.com/us](http://www.nora.com/us)

**nora**<sup>®</sup>  
by Interface<sup>®</sup>