

# nora<sup>®</sup> PU 102

2-part polyurethane adhesive

nora<sup>®</sup> PU 102 is a two-component urethane adhesive designed specifically for the installation of specific nora<sup>®</sup> rubber floor coverings on suitable substrates. When parts A & B are thoroughly mixed together they form a reactive adhesive that cures to a tough, flexible film with a good resistance to surface moisture and many chemicals. Also part of the nora one<sup>®</sup> system solution.

- Non-flammable and freeze/thaw stable
- Free of organic solvents, formaldehyde, asbestos, lindane, rosins, plasticizers or any other volatile components
- Meets the South Coast (CA) Air Quality Management District Rule 1168
- Meets VOC emissions and content requirements of LEED, including REACH

## nora PU 102 – Art. 6696

Shelf Life	12 Months
Application	1/32" x 1/16" x 1/32" U-notch trowel
Coverage	~170 - 190 square feet per 1 gallon
Open Time	20 - 45 Minutes
Working Time	120 Minutes
Storage	Room temperature and away from direct sunlight
Moisture Limit	≤ 85% RH following ASTM F2170 <i>Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using in situ Probes</i>
Freeze/Thaw stable	Stable per ASTM D7149 at 0°F (-18°C)

For information on the nora one<sup>®</sup> system solution visit [www.nora.com/us/noraone](http://www.nora.com/us/noraone)

### nora systems, Inc.

9 Northeastern Blvd.  
Salem, NH 03079  
Toll free: 800-332-NORA  
Phone: (603) 894-1021  
Fax: (603) 894-6615  
E-mail: [info-us@nora.com](mailto:info-us@nora.com)  
[www.nora.com/us](http://www.nora.com/us)

**nora**<sup>®</sup>  
by Interface<sup>®</sup>