

nora dryfix 750

Double-sided dry adhesive tape for the installation of specific nora floor coverings, providing a reliable alternative to conventional flooring adhesives. It is easy to install with no mixing or adhesive cleanup and allows for immediate traffic post-installation.



Product Construction Specifications

Product: nora dryfix™ 750, Article 502905

Material Composition: A quick and easy dry adhesive tape used to install specific nora® rubber floor coverings (2 mm – 4 mm).

Material Description/Size: 75 cm x 30 m (~29.5 in x 98.5 ft) dry adhesive tape with a releasable wax paper in a white cardboard box.

Performance Standards

Shelf Life:	24 months
Coverage:	~242 SF per roll
Moisture Limit:	≤ 85% RH following ASTM F2170 <i>Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using in situ Probes</i>
Freeze/Thaw stable:	Stable per ASTM D7149 at 0°F (- 18°C)

Health + Environmental Specifications

Indoor Air Quality: GREENGUARD Gold Certified for low VOC emissions in compliance with CDPH 01350.

LEED v4: Contributes to IEQ credits

Material Composition: Free of organic solvents, formaldehyde, asbestos, lindane, rosins, phthalates, or any other volatile components.

VOC Content: 0 grams/liter. In compliance with the SCAQMD Rule 1168 Standard for Rubber Floor Adhesives, which has a VOC limit of 60 grams/liter.

Installation

Site Conditions: The installation area must be fully enclosed, weather tight, and climate controlled between 63°F and 75°F and 40% to 60% ambient relative humidity (RH) for at least 48 hours prior, during and 72 hours after installation.

Substrate Requirements: Concrete, wood, metal, and existing floors (existing floors must be only one layer and non-cushioned back); refer to the nora Installation Instructions for details.

Unique Characteristics:

- Excellent for heavy traffic and heavy rolling loads (no forklift traffic)
- Odorless
- Suitable for all common substrates
- Reliable in high performance areas
- No necessary open time required
- Non-flammable and freeze/thaw stable
- Less downtime with immediate trafficking after installation
- If specified, hot or cold welding of flooring can commence immediately (areas that are not climate controlled must be welded)

For complete installation instructions refer to the nora Installation Instructions.

Disclaimer

It is the user's responsibility to read, understand and follow the nora Installation Instructions, Product Data Sheet, and Safety Data Sheet available on www.nora.com. You should comply with all applicable OSHA, local, state, and federal regulations.

Storage

Room temperature and away from direct sunlight.

Post-Installation Traffic

- All traffic is allowed immediately post-installation.

Contact the nora Technical Department for confirmation of adhesive and flooring limits.

Warranty

Refer to the nora Limited Warranty - Americas.

Current nora Installation Instructions, Guide Specifications, Maintenance Guidelines, and Limited Warranties can be found at www.nora.com.

nora®, norament®, and noraplan® are trademarks owned by nora systems GmbH and registered in the United States, Canada, and other countries. All other trademarks are the property of their respective owners.

Updated: April 2024