

nora[®] dryfix 750

ADHESIVE TAPE

nora[®] dryfix 750 provides a safe, healthy, cost and time-efficient alternative to conventional flooring adhesives. There is no mixing or adhesive clean-up necessary, and nora dryfix 750 allows for immediate traffic post-installation.

- Odorless
- Recommended for operating rooms
- Excellent for heavy traffic
- No necessary open time required
- Non-flammable and freeze/thaw stable
- Free of organic solvents, formaldehyde, asbestos, lindane, rosins, plasticizers or any other volatile components
- Meets the South Coast (CA) Air Quality Management District Rule 1168



Product Data

Product	nora [®] dryfix 750, Article 502905
Description	nora dryfix 750 is easy and fast-to-use dry adhesive tape with a fabric carrier that is used to install specific nora [®] floor coverings (2 mm – 4 mm).
Characteristics	Size: 29.5 inches by 98.5 feet (75 cm x 30 m) tape covered by white wax paper. Packaging: White cardboard box.

Technical Data

Shelf Life	24 Months
Coverage	242 square feet per roll
Storage	Room temperature and away from direct sunlight
Moisture Limit	≤ 85% RH following ASTM F2170 <i>Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using in situ Probes</i>
Freeze/Thaw stable	Stable per ASTM D7149 at 0°F (- 18°C)

Environmental Attributes

VOC Emissions	Greenguard Gold certified for low VOC emissions in compliance with California Department of Public Health (CDPH) Standard Method v1.1-2010
VOC Content	0 grams/liter; product is in compliance with the SCAQMD Rule 1168 Standard for Rubber Floor Adhesives, which has a VOC limit of 60 grams/liter
LEED Contribution	Meets VOC emissions and content requirements of LEED

Installation

Site Conditions	The installation area must be fully enclosed, weather tight, and climate controlled between 63°F and 75°F and 40% to 60% ambient relative humidity (RH) for at least 48 hours prior, during and 72 hours after installation.
Substrate Requirements	Concrete, wood, metal and existing floors (existing floors must be only one layer and non-cushioned back); refer to the nora® Installation Guide for details.
Unique Characteristics	Installation area can be returned to service immediately. Hot or cold welding of flooring can commence immediately. Areas that are not climate controlled must be welded.

For complete installation instructions, refer to the nora Installation Guide.

Disclaimer

It is the user's responsibility to read, understand and follow the nora Installation Guide, Product Data Sheet and Safety Data Sheet available on www.nora.com/us. You should comply with all applicable OSHA, local, state and federal regulations.

Traffic

All traffic is allowed immediately post-installation.

Withstands heavy foot traffic and heavy rolling loads. No fork lift traffic.

Contact the nora® Technical Department for confirmation of adhesive and flooring limits.

Warranty

See nora® Limited Warranty.

For current nora® Installation Guides, Guide Specifications, Maintenance Guides, and Limited Warranties, please visit www.nora.com/us.

Dated: November 2018

nora systems, Inc.

9 Northeastern Blvd.

Salem, NH 03079

Toll free: 800-332-NORA

Phone: (603) 894-1021

Fax: (603) 894-6615

E-mail: info-us@nora.com

www.nora.com/us