

nora liquid wax

A solvent free wax emulsion used as a separation layer, ensuring excess weld does not bond to the flooring surface when cold welding nora® floor coverings.

Product Data

Product: nora® liquid wax, Article 109914

Description: A solvent-free wax emulsion.

Characteristics:

- Size/description: 16-ounce white plastic bottle.



Technical Data

Shelf Life:	Use within 12 Months of opening
Application:	Clean cloth
Coverage:	~ 675 feet at 4 inches wide
Dry Time:	~ 5-10 minutes
Storage:	Room temperature and away from direct sunlight
Freeze/Thaw stable:	Stable per ASTM D7149 at 0°F (- 18°C)

Environmental Attributes

Carbon: All flooring products 3rd party verified carbon neutral throughout their entire life cycle through the Interface Carbon Neutral Floors™ program. Learn more at www.interface.com/carbonneutral.

Material Composition: Free of organic solvents, formaldehyde, asbestos, lindane, rosins, phthalates, or any other volatile components.

Installation

Site Conditions: The installation area must be fully enclosed, weather tight, and climate controlled between 63°F and 75°F and 40% to 60% ambient relative humidity (RH) for at least 48 hours prior, during and 72 hours after installation.

Unique Characteristics:

- Non-flammable and freeze/thaw stable
- Used as a release agent prior to the cold welding of norament® flooring
- Can also be used as a separation layer on tools and adhesive trowels

For complete installation instructions refer to the nora Installation Instructions.

Disclaimer

It is the user's responsibility to read, understand and follow the nora Installation Instructions, Product Data Sheet, and Safety Data Sheet available on www.nora.com. You should comply with all applicable OSHA, local, state, and federal regulations.

Clean-up

Removed during initial cleaning: To remove nora liquid wax from nora flooring coverings after the nora® cold weld is fully cured, wet mop the floor using a high-pH cleaner (12–13pH) solution diluted as per the manufacturer's mixing instructions. Allow the solution a minimum dwell time of 10 minutes. Scrub the floor thoroughly with a floor scrubber as outlined in the nora Maintenance Guidelines.

Disposal

Dispose in accordance with local, state, and national regulations. Where possible, collect product residues and reuse. Do not allow product to get into drains, watercourses, or landfill. Collect any remaining waste material, mix both components and allow to harden, and then dispose of as Construction Waste.

Warranty

Refer to the nora Product Warranty - Americas.

Current nora Installation Instructions, Guide Specifications, Maintenance Guidelines, and Product Warranties can be found at www.nora.com.

nora®, norament®, and noraplan® are trademarks owned by nora systems GmbH and registered in the United States, Canada, and other countries. All other trademarks are the property of their respective owners.

Updated: June 2022