

nora[®] liquid wax

ACCESSORY

The nora[®] liquid wax is a solvent free wax emulsion used as a separation layer to ensure, during the norament[®] and noraplan[®] cold welding process, excess weld does not bond to the flooring surface.

- Non-flammable and freeze/thaw stable
- Free of organic solvents, formaldehyde, asbestos, lindane, rosins, plasticizers or any other volatile components
- Meets the South Coast (CA) Air Quality Management District Rule 1168



Product Data

Product	nora [®] liquid wax
Description	nora [®] liquid wax is a solvent free wax emulsion
Characteristics	16 oz. white plastic bottle

Technical Data

Shelf Life	Use within 12 months of opening
Application	Clean cloth
Coverage	675 feet at 4 inches wide
Dry Time	~ 5-10 minutes
Storage	Room temperature and away from direct sunlight
Freeze/Thaw stable	Stable per ASTM D7149 at 0°F (- 18°C).

Installation

Site Conditions	The installation area must be fully enclosed, weather tight, and climate controlled between 63°F and 75°F and 40% to 60% ambient relative humidity (RH) for at least 48 hours prior, during and 72 hours after installation.
Unique Characteristics	Used as a release agent prior to the cold welding of norament flooring. nora liquid wax may also be used as a separation layer on tools, adhesive trowels.

For complete installation instructions, refer to the nora[®] Installation Guide.

Disclaimer

It is the user's responsibility to read, understand and follow the nora Installation Guide, Product Data Sheet and Safety Data Sheet available on www.nora.com/us. You should comply with all applicable OSHA, local, state and federal regulations.

Clean-up

Removed during initial cleaning: To remove nora liquid wax from nora flooring coverings after the nora[®] cold weld is fully cured, wet mop the floor using a high-pH cleaner (12–13pH) solution diluted as per the manufacturer's mixing instructions. Allow the solution a minimum dwell time of 10 minutes. Scrub the floor thoroughly with a floor scrubber as outlined in the nora[®] Maintenance Guides.

Disposal

Dispose in accordance with local, state and national regulations. Where possible, collect product residues and reuse. Do not allow product to get into drains, watercourses or landfill. Collect any remaining waste material, mix both components and allow to harden, and then dispose of as construction waste.

Traffic

Heavy Foot traffic is allowed after 24 hours.

Contact the nora[®] Technical Department for confirmation of adhesive and flooring limits.

Warranty

See nora[®] Limited Warranty.

For current nora[®] Installation Guides, Guide Specifications, Maintenance Guides, and Limited Warranties, please visit www.nora.com/us.

Updated: November 2018

nora systems, Inc.

9 Northeastern Blvd.

Salem, NH 03079

Toll free: 800-332-NORA

Phone: (603) 894-1021

Fax: (603) 894-6615

E-mail: info-us@nora.com

www.nora.com/us