

nora[®] nTx 020

ACCESSORY

nora[®] nTx 020 is a 1-component Polyurethane resin surface bond enhancer for use with the nora[®] nTx system on absorptive and non-absorptive substrates.

- Ready to use
- Fast drying
- Alkali resistant
- Solvent free
- Ready for installation in about 1 hour
- Superior bonding to a wide range of substrates



Product Data

Product	nora [®] nTx 020, Article 502904
Description	nora nTx 020 is a 1-component Polyurethane resin surface bond enhancer
Characteristics	Red liquid , 2.6 gallon white plastic container

Technical Data

Shelf Life	12 months
Application	micro fiber roller and paint tray
Coverage	1200 sq. ft. per 2.6 gal. unit; coverage will vary based on substrate conditions
Working Time	20 - 40 minutes
Dry Time	60 – 90 minutes must be tack free
Storage	Room temperature in a dry area away from direct sunlight
Moisture Limit	100% RH following ASTM F2170 <i>Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using in situ Probes</i>
Freeze/Thaw stable	Stable per ASTM D7149

Environmental Attributes

VOC Emissions	Greenguard Gold certified for low VOC Emissions in compliance with California Department of Public Health (CDPH) Standard Method v1.1-2010
VOC Content	< 15 grams/liter; product is in compliance with the SCAQMD Rule 1168 Standard for Primers, which has a VOC limit of 250 grams/liter.
LEED Contribution	Meets VOC emissions and content requirements of LEED

Installation Requirements

Site Conditions	The installation area must be fully enclosed, weather tight, and climate controlled between 63°F and 75°F and 40% to 65% ambient relative humidity (RH) for at least 48 hours prior, during and 72 hours after application.
Substrate Requirements	The subfloor must be structurally sound, solid, dry, free from active cracks, clean and free of all contaminants such as grease, oil, paint, wax, curing, and sealing compounds that would impair adhesion. Refer to the nora® nTx Installation Guide for details.
Unique Characteristics	No moisture limit or RH testing required Moisture resistant smoothing compounds must be used under nora nTx 020 in high moisture installations

For complete installation instructions, refer to the nora nTx Installation Guide.

Disclaimer

It is the user's responsibility to read, understand and follow the nora® nTx Installation Guide, Product Data Sheet and Safety Data Sheet available on www.nora.com/us. You should comply with all applicable OSHA, local, state and federal regulations.

Clean-up

Immediately clean all tools, equipment, or spilled nora nTx 020 with 70% isopropyl alcohol and clean cloth. Once cured this material can only be mechanically removed and may cause damage to some surfaces.

Disposal

Dispose in accordance with local, state and federal regulations. Do not allow product to get into drains, watercourses or landfill. Hardened product residues are considered construction waste. Empty packaging is recyclable.

Traffic

Prevent all traffic until dry and tack free.

Warranty

See nora® nTx Limited Warranty.

For current nora® Installation Guides, Guide Specifications, Maintenance Guides, and Limited Warranties, please visit www.nora.com/us.

Updated: November 2018

nora systems, Inc.

9 Northeastern Blvd.
Salem, NH 03079
Toll free: 800-332-NORA
Phone: (603) 894-1021
Fax: (603) 894-6615
E-mail: info-us@nora.com
www.nora.com/us