

nora[®] profix

ADHESIVE TAPE

nora[®] profix is an easy and fast-to-use tape used to install nora[®] sanitary base and flash coving.

- Odorless
- No necessary open time required
- Non-flammable and freeze/thaw stable
- Free of organic solvents, formaldehyde, asbestos, lindane, rosins, plasticizers or any other volatile components
- Meets the South Coast (CA) Air Quality Management District Rule 1168



Product Data

Product	nora [®] profix, Articles 502907 (145), 502908 (90), & 502910 (50)
Description	nora profix is an easy and fast-to-use dry adhesive tape used to install specific nora [®] flooring products.
Characteristics	<p>Size:</p> <p>nora profix 145, 5.71 inches wide x 164 feet (145 mm x 50 m) covered by wax paper</p> <p>nora profix 90, 3.54 inches wide x 164 feet (90 mm x 50 m) covered by wax paper</p> <p>nora profix 50, 1.97 inches wide x 164 feet (50 mm x 50 m) covered by wax paper</p> <p>Packaging: White cardboard box.</p>

Technical Data

Shelf Life	1 year minimum
Coverage	<p>nora profix 145 - 78 sq. ft.</p> <p>nora profix 90 - 48.4 sq. ft.</p> <p>nora profix 50 - 26.9 sq. ft.</p>
Storage	Room temperature and away from direct sunlight
Moisture Limit	≤ 75% RH following ASTM F2170 <i>Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using in situ Probes</i>
Freeze/Thaw stable	Stable per ASTM D7149 at 0°F (- 18°C)

Environmental Attributes

VOC Emissions	Greenguard Gold certified for low VOC emissions in compliance with California Department of Public Health (CDPH) Standard Method v1.1-2010
VOC Content	0 grams/liter; product is in compliance with the SCAQMD Rule 1168

	Standard for Rubber Floor Adhesives, which has a VOC limit of 60 grams/liter
LEED Contribution	Meets VOC emissions and content requirements of LEED

Installation

Site Conditions	The installation area must be fully enclosed, weather tight, and climate controlled between 63°F and 75°F and 40% to 60% ambient relative humidity (RH) for at least 48 hours prior, during and 72 hours after installation.
Substrate Requirements	Concrete, wood, metal; refer to the nora® Installation Guide for details. Dry wall must be dust free and painted or primed.
Unique Characteristics	Do not use with wall base Installation area can be returned to service immediately Hot or cold welding of flooring can commence immediately

For complete installation instructions, refer to the nora Installation Guide.

Disclaimer

It is the user's responsibility to read, understand and follow the nora Installation Guide, Product Data Sheet and Safety Data Sheet available on www.nora.com/us. You should comply with all applicable OSHA, local, state and federal regulations.

Traffic

All traffic is allowed immediately post-installation.

Withstands heavy foot traffic and heavy rolling loads. No fork lift traffic.

Contact nora technical for confirmation of adhesive and flooring limits.

Warranty

See nora® Limited Warranty.

For current nora® Installation Guides, Guide Specifications, Maintenance Guides, and Limited Warranties, please visit www.nora.com/us.

Updated: November 2018

nora systems, Inc.

9 Northeastern Blvd.

Salem, NH 03079

Toll free: 800-332-NORA

Phone: (603) 894-1021

Fax: (603) 894-6615

E-mail: info-us@nora.com

www.nora.com/us