

# nora<sup>®</sup> PRP 101

## PRIMER (absorptive substrates)

nora<sup>®</sup> PRP 101 is a fast drying primer for absorptive surfaces. Used as a bonding agent on absorptive substrates prior to installing nora<sup>®</sup> L 1000 leveler.

- Water based
- Solvent free
- Meets the South Coast (CA) Air Quality Management District Rule 1168



### Product Data

Product	nora <sup>®</sup> PRP 101, Article 6699
Description	nora PRP 101 is a fast drying primer for absorptive surfaces.
Characteristics	White liquid; 2.5 gallon white container

### Technical Data

Shelf Life	12 Months
Application	Micro fiber roller
Coverage	~ 875 – 1300 sq. ft. per 2.5 gallon unit
Storage	Room temperature and away from direct sunlight
Moisture Limit	≤ 85% RH following ASTM F2170 <i>Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using in situ Probes</i>
Freeze/Thaw stable	Keep from freezing

### Environmental Attributes

VOC Content	< 42 grams/liter; product is in compliance with the SCAQMD Rule 1168 Standard for Architectural sealants, which has a VOC limit of 250 grams/liter
LEED Contribution	Meets VOC content requirements of LEED

### Installation Requirements

Site Conditions	The installation area must be fully enclosed, weather tight, and climate controlled between 63°F and 75°F and 40% to 60% ambient relative humidity (RH) for at least 48 hours prior, during and 72 hours after installation.
Substrate Requirements	Clean concrete; refer to the nora <sup>®</sup> Installation Guide for details.
Unique Characteristics	Do not dilute

For complete installation instructions, refer to the nora Installation Guide.

## **Disclaimer**

It is the user's responsibility to read, understand and follow the nora Installation Guide, Product Data Sheet and Safety Data Sheet available on [www.nora.com/us](http://www.nora.com/us). You should comply with all applicable OSHA, local, state and federal regulations.

## **Clean-up**

Immediately clean from tools and any surface using soap, water and a clean cloth. Once cured, dried primer is difficult to remove.

## **Disposal**

Dispose in accordance with local, state and federal regulations.

## **Traffic**

Foot traffic is allowed after dry and tack free, ~ 30 to 60 minutes.

## **Warranty**

See nora® Limited Warranty.

For current nora® Installation Guides, Guide Specifications, Maintenance Guides, and Limited Warranties, please visit [www.nora.com/us](http://www.nora.com/us).

*Dated: November 2018*

### **nora systems, Inc.**

9 Northeastern Blvd.

Salem, NH 03079

Toll free: 800-332-NORA

Phone: (603) 894-1021

Fax: (603) 894-6615

E-mail: [info-us@nora.com](mailto:info-us@nora.com)

[www.nora.com/us](http://www.nora.com/us)