

nora[®] stepfix

ADHESIVE TAPE

Specifically developed for norament[®] stairtreads, nora[®] stepfix makes installing stairtreads quick, clean, and easily manageable – making nora stepfix the optimum solution.

- Odorless
- No necessary open time required
- Non-flammable and freeze/thaw stable
- Free of organic solvents, formaldehyde, asbestos, lindane, rosins, plasticizers or any other volatile components
- Meets the South Coast (CA) Air Quality Management District Rule 1168



Product Data

Product	nora [®] stepfix, Article 502906
Description	nora stepfix is easy and fast-to-use dry adhesive tape with a that is used to install norament stairtreads.
Characteristics	Size: 9.45 inches x 164 feet (240 mm x 50 m) covered with wax paper Packaging: White cardboard box

Technical Data

Shelf Life	1 year minimum
Coverage	129 sq. ft. per roll
Storage	Room temperature and away from direct sunlight
Moisture Limit	≤ 75% RH following ASTM F2170 <i>Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using in situ Probes</i>
Freeze/Thaw stable	Stable per ASTM D7149 at 0°F (- 18°C)

Environmental Attributes

VOC Emissions	Greenguard Gold certified for low VOC emissions in compliance with California Department of Public Health (CDPH) Standard Method v1.1-2010
VOC Content	0 grams/liter; product is in compliance with the SCAQMD Rule 1168 Standard for Rubber Floor Adhesives, which has a VOC limit of 60 grams/liter
LEED Contribution	Meets VOC emissions and content requirements of LEED

Installation

Site Conditions	The installation area must be fully enclosed, weather tight, and climate controlled between 63°F and 75°F and 40% to 60% ambient relative humidity (RH) for at least 48 hours prior, during and 72 hours after installation.
Substrate Requirements	Concrete, wood, metal; refer to the nora [®] Installation Guide for details.

Unique Characteristics	Easily dry-fit the tread right on the covered adhesive tape, and stairs can be walked on immediately following installation Installation area can be returned to service immediately 2 foot length of nora stepfix required for each liner foot of stair tread
------------------------	--

For complete installation instructions, refer to the nora Installation Guide.

Disclaimer

It is the user's responsibility to read, understand and follow the nora Installation Guide, Product Data Sheet and Safety Data Sheet available on www.nora.com/us. You should comply with all applicable OSHA, local, state and federal regulations.

Traffic

All traffic is allowed immediately post-installation.

Withstands heavy foot traffic and heavy rolling loads. No fork lift traffic.

Contact nora® Technical Department for confirmation of adhesive and flooring limits.

Warranty

See nora® Limited Warranty.

For current nora® Installation Guides, Guide Specifications, Maintenance Guides, and Limited Warranties, please visit www.nora.com/us.

Updated: November 2018

nora systems, Inc.

9 Northeastern Blvd.

Salem, NH 03079

Toll free: 800-332-NORA

Phone: (603) 894-1021

Fax: (603) 894-6615

E-mail: info-us@nora.com

www.nora.com/us