

nora[®] DPM 100

2-part epoxy damp proof membrane

noraONE

nora one[®] system components are only eligible for jobs that meet the minimum requirements of 50,000 square feet.

nora[®] DPM 100 is a two-component 100% solids epoxy moisture control system that is formulated for concrete substrates, and offers low viscosity, high-density resins which penetrate deep into the substrate.

- Reduced odor during application
- Non-flammable and freeze/thaw stable
- High barrier effect
- Fast curing
- Meets the South Coast (CA) Air Quality Management District Rule 1168
- Meets VOC content requirements of LEED, including REACH

nora DPM 100 – Art. 6701

Shelf Life	12 Months
Application	1/8" x 1/8" x 1/8" notched squeegee and loop pile roller
Coverage	270 square feet per 2.5 gallon unit based on CSP 3
Pot Life	10 - 15 Minutes
Working Time	25 - 30 Minutes
Storage	Room temperature and away from direct sunlight
Moisture Limit	Up to 100% RH following ASTM F2170 <i>Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using in situ Probes</i>
Freeze/Thaw stable	Stable per ASTM D7149 at 0°F (-18°C)

For information on the nora one[®] system solution visit www.nora.com/us/noraone

nora systems, Inc.
9 Northeastern Blvd.
Salem, NH 03079
Toll free: 800-332-NORA
Phone: (603) 894-1021
Fax: (603) 894-6615
E-mail: info-us@nora.com
www.nora.com/us

nora[®]
by Interface[®]

01/2019