

nora[®] SP 111

Moisture resistant skimcoating and patching compound

nora[®] ONE

nora one[®] system components are only eligible for jobs that meet the minimum requirements of 50,000 square feet.

nora[®] SP 111 is designed to repair substrate imperfections prior to the installation of nora[®] rubber flooring. nora SP 111 is used as a skim coat from featheredge. Flooring can be installed when the nora SP 111 is used as skim coat in as little as 15 - 20 minutes (thick applications will take longer).

- Fast dry formula
- Ideal for smoothing minor imperfections and holes.
- Up to 1 inch deep in one application
- Superior bonding to a wide range of substrates
- Meets VOC content requirements of LEED, including REACH

nora SP 111 – Art. 6702

| | |
|----------------|---|
| Shelf Life | 9 Months |
| Application | Flat steel finishing trowel |
| Coverage | 28 sq. ft. at 1/8" depth, per 10 lb. bag; coverage will vary based on substrate conditions |
| Water Ratio | 2.5 quarts per bag or mix two parts powder to one part water |
| Working Time | 10 - 15 minutes, thick applications will take longer |
| Storage | Room temperature and away from direct sunlight |
| Moisture Limit | Up to 100% RH following ASTM F2170 <i>Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using in situ Probes</i> |

For information on the nora one[®] system solution visit www.nora.com/us/noraone

nora systems, Inc.
9 Northeastern Blvd.
Salem, NH 03079
Toll free: 800-332-NORA
Phone: (603) 894-1021
Fax: (603) 894-6615
E-mail: info-us@nora.com
www.nora.com/us

nora[®]
by Interface[®]

01/2019