

SECTION 1: IDENTIFICATION

Trade name: nora® SP 111

- Application of the substance / the mixture: Moisture resistant skimcoating and patching compound
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
nora systems, Inc.
9 Northeastern Blvd.
Salem, NH 03079
Toll-Free: 800-332-NORA
- Information department: see Manufacturer/Supplier
- Emergency telephone number: 800-424-9300 CHEMTREC

SECTION 2: HAZARD(S) IDENTIFICATION

- Classification of the substance or mixture



GHS08 Health hazard

Carc. 1A H350 May cause cancer. Route of exposure: Inhalation.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.

- Label elements
- GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms GHS05, GHS08
- Signal word Danger
- Hazard-determining components of labeling:

Portland cement

Quartz (crystalline silica)

- Hazard statements

Causes serious eye damage.

May cause cancer. Route of exposure: Inhalation.

Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

- Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN: Wash with plenty of soap and water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

nora® SP 111

Safety Data Sheet

acc. to OSHA HCS

IF exposed or concerned: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations

· NFPA ratings (scale 0 - 4)



Health = 2

Flammability = 1

Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH	2
FIRE	1
REACTIVITY	0

Health = 2

Flammability = 1

Reactivity = 0

· Other hazards

NFPA Rating Scale: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe.

NFPA is the National Fire Protection Association.

HMIS Rating Scale: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe.

HMIS®, the Hazardous Materials Identification System, is a registered mark of the National Paint and Coatings Association (NPCA).

* Chronic health effect possible - inhalation of silica dust may cause lung injury/disease (silicosis). Take appropriate measures to avoid breathing dust. See sections 3, 8 and 11.

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Hazardous ingredients:		
CAS: 7778-18-9	Calcium sulphate (gypsum)	10 - <25%
CAS: 65997-15-1	Portland cement	5 - <10%
	☠ Eye Dam. 1, H318; ☠ Skin Irrit. 2, H315; STOT SE 3, H335	
CAS: 14808-60-7	Quartz (crystalline silica)	<1.0%
	☠ Carc. 1A, H350; STOT RE 1, H372	

· Additional information:

The exact percentages of the ingredients have been withheld by the manufacturer as trade secrets.

Note: Crystalline silica (quartz) is not intentionally added to this product, but may be a naturally occurring impurity in other inorganic fillers used in this product.

nora® SP 111

Safety Data Sheet

acc. to OSHA HCS

The amount of respirable crystalline silica is less than 0.1 %.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: FIRST-AID MEASURES

· Description of first aid measures

· General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

· After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Call a doctor.

· After swallowing: Do not induce vomiting; immediately call for medical help.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: FIRE-FIGHTING MEASURES

· Extinguishing media

· Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

· Special hazards arising from the substance or mixture No further relevant information available.

· Advice for firefighters

· Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: ACCIDENTAL RELEASE MEASURES

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Wear dust mask.

Avoid formation of dust.

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Use an industrial vacuum cleaner with a high efficiency (HEPA-) filter to clean up dust.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:

nora® SP 111

Safety Data Sheet

acc. to OSHA HCS

CAS: 14808-60-7 Quartz (crystalline silica) 0.075 mg/m³

· PAC-2:

CAS: 14808-60-7 Quartz (crystalline silica) 33 mg/m³

· PAC-3:

CAS: 14808-60-7 Quartz (crystalline silica) 200 mg/m³

SECTION 7: HANDLING AND STORAGE

· Handling:

· Precautions for safe handling

Prevent formation of dust.

Wear suitable protective clothing, gloves and eye/face protection.

When mixing wear suitable NIOSH-approved dust respirator.

Avoid contact with the eyes and skin.

Provide appropriate exhaust ventilation at places where airborne dust is generated. In case of insufficient ventilation, wear suitable respiratory protective equipment (e.g. NIOSH-approved dust respirator).

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: Keep receptacle tightly sealed.

· Information about storage in one common storage facility: Store away from foodstuffs.

· Further information about storage conditions:

Store in dry conditions.

Protect from humidity and water.

· Specific end use(s) No further relevant information available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

· Additional information about design of technical systems:

Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits.

Ventilation should effectively remove and prevent buildup of any dust generated from the handling of this product.

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 7778-18-9 Calcium sulphate (gypsum)

PEL Long-term value: 15* 5** mg/m³
*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³
*total dust **respirable fraction

TLV Long-term value: 10* mg/m³
*as inhalable fraction

CAS: 65997-15-1 Portland cement

nora® SP 111

Safety Data Sheet

acc. to OSHA HCS

PEL	Long-term value: 50 mppcf or 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³
TLV	*total dust **respirable fraction Long-term value: 1* mg/m ³
CAS: 14808-60-7 Quartz (crystalline silica)	
PEL	see Quartz listing
REL	Long-term value: 0.05* mg/m ³
TLV	*respirable dust; See Pocket Guide App. A Long-term value: 0.025* mg/m ³

- Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:
 - Prevent formation of dust.
 - Wear suitable protective clothing, gloves and eye/face protection.
 - Avoid contact with the eyes and skin.
 - Keep away from foodstuffs, beverages and feed.
 - Wash hands before breaks and at the end of work.
- Respiratory protection:
 - When mixing wear suitable NIOSH-approved dust respirator.
 - Provide appropriate exhaust ventilation at places where airborne dust is generated. In case of insufficient ventilation, wear suitable respiratory protective equipment (e.g. NIOSH-approved dust respirator).
- Protection of hands:



Use nitrile impregnated cotton-gloves

- Material of gloves Nitrile impregnated cotton-gloves
- Penetration time of glove material
 - The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- Eye protection: Safety glasses

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

· Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Solid
Color:	Gray
· Odor:	Light
· Odor threshold:	Not determined.
· pH-value at 20 °C (68 °F):	11
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.

nora® SP 111

Safety Data Sheet

acc. to OSHA HCS

· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not determined.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not self-igniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not applicable.
· Density:	Not determined.
· Relative density	Not determined.
· Vapor density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Insoluble. Sets with water.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Other information	No further relevant information available.

SECTION 10: STABILITY AND REACTIVITY

- Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: TOXICOLOGICAL INFORMATION

- Information on toxicological effects
- Acute toxicity:
- Specific symptoms in biological assay:
- Primary route(s) of entry: Inhalation, skin contact, eye contact.
- Primary irritant effect:
- on the skin: Slightly irritant effect may occur.
- on the eye: Strong irritant with the danger of severe eye injury.
- Sensitization:
No sensitizing effects known.
Low in Chromate (< 2 ppm) acc. Regulation (EC) No 1907/2006 (REACH).

nora® SP 111

Safety Data Sheet

acc. to OSHA HCS

· Subacute to chronic toxicity:

Respirable crystalline silica (quartz) may cause a severe lung disease named silicosis. Symptoms of silicosis may be a shortness of breath, fever or cough. Silicosis is reported to increase the risk of carcinogenicity caused by continuous inhalation of respirable crystalline silica. Though the product itself contains less than

0.1% of respirable crystalline silica, respirable silica may be generated from working procedures such as grinding e.g. In general, inhalation of silica dust should be avoided. Therefore, for your own safety wear a suitable NIOSH-approved respirator in all occasions when handling of the product generates dust.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
CAS: 14808-60-7	Quartz (crystalline silica)	1
· NTP (National Toxicology Program)		
CAS: 14808-60-7	Quartz (crystalline silica)	K
· OSHA-Ca (Occupational Safety & Health Administration)		
CAS: 14808-60-7	Quartz (crystalline silica)	

SECTION 12: ECOLOGICAL INFORMATION

· Toxicity

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes: Do not allow product to reach ground water, water course or sewage system.
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

SECTION 13: DISPOSAL CONSIDERATIONS

- Waste treatment methods
- Recommendation:
Do not allow product to reach sewage system.
Mix product residues with water, allow to harden, then dispose of as construction waste.
- Uncleaned packagings:
- Recommendation: Empty paper packaging is recyclable.

SECTION 14: TRANSPORT INFORMATION

· DOT, ADR, ADN, IMDG, IATA	Void
· UN proper shipping name	
· DOT, ADR, ADN, IMDG, IATA	Void
· DOT, ADN, IMDG, IATA	
· Class	Void

nora® SP 111

Safety Data Sheet

acc. to OSHA HCS

· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport/Additional information:	Not regulated as hazardous material according to the above specifications.
· UN "Model Regulation":	Void

SECTION 15: REGULATORY INFORMATION

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- SARA (Superfund Amendments and Reauthorization Act)

· EPCRA Section 302 (Extremely Hazardous Substances):
None of the ingredient is listed.
· SARA Title III Section 313 (Toxic Release Inventory - TRI):
None of the ingredients is listed.
· TSCA (Toxic Substances Control Act):
All ingredients are listed.

- Proposition 65 (California)
- Chemicals known to cause cancer:
Crystalline silica (quartz) is classified as a substance known to the State of California to be a carcinogen.

CAS: 14808-60-7	Quartz (crystalline silica)
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	

- Carcinogenicity categories

· EPA (Environmental Protection Agency)		
None of the ingredients is listed		
· TLV (Threshold Limit Value established by ACGIH)		
CAS: 14808-60-7	Quartz (crystalline silica)	A2
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
CAS: 14808-60-7	Quartz (crystalline silica)	

- GHS label elements
The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms GHS05, GHS08
- Signal word Danger
- Hazard-determining components of labeling:
Portland cement
Quartz (crystalline silica)
- Hazard statements
Causes serious eye damage.
May cause cancer. Route of exposure: Inhalation.

nora® SP 111

Safety Data Sheet

acc. to OSHA HCS

Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Do not breathe dust.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN: Wash with plenty of soap and water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 16: OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Contact: see Manufacturer/Supplier

· Date of preparation / last revision: 11/24/2017

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Carc. 1A: Carcinogenicity – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1