

nora® nTx 020

1C primer



* Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



Primer for improved adhesion. Use nora® nTx 020 only for installing nora® nTx floor coverings.

- **Substrate preparation:** The substrate and climatic conditions must meet the requirements according to DIN 18 356 and DIN 18 365. The substrate can be dry or moist, but must be firm, load-bearing, frost-proof, and free of dust and separating agents. nora® nTx 020 must be applied twice to fresh cement substrates with excess residual moisture.
- **Application:** Shake well before use. Pour the primer into a clean vessel, and apply within 60 minutes. It is applied with a short pile roller. The working temperature may not fall below +10 °C. Low temperatures and/or high air humidity may extend the setting time.
- **Drying time:** Approx. 1 h as priming layer
- **Working time:** Approx. 60 min. at +20 °C
- **Accessibility:** After about 40 - 50 min. at +20 °C
- **Usage:** 100 - 150 g/m² for a single application, 250 - 300 g/m² for two applications
- **Cleaning:** Clean the tools with water
- **Storage:** Approx. 12 months in original sealed packaging. Do not store under +5 °C, frost sensitive.
- **Disposal:** Introduce only completely empty packaging to recycling processes. Cured residue may be disposed of as industrial waste similar to domestic waste. Industrial waste disposal e.g. EAK no. 17 09 04 (construction and demolition waste) or EAK no. 08 04 10 (adhesives and sealing compounds).
- **Underfloor heating suitability:** Yes
- **EMICODE:** EC1R+ (very low emission levels ^{PLUS})
- **GISCODE RU 1**
- **Packaging:** Canister of 11 kg

General:

Many circumstances are beyond our control. In all cases, we recommend adequate tests. Please consult the applicable nora® nTx installation recommendations, the technical product details, the safety data sheet, and our delivery and payment terms.

Product EXCLUSIVELY for the professional processor

Made in Germany