Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Revision Date: 05/11/2015



SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture Product Name: nora® 310 B

1.2. Intended Use of the Product

Use of the Substance/Mixture: No use is specified.

1.3. Name, Address, and Telephone of the Responsible Party

Company

nora systems, Inc. 9 Northeastern Blvd Salem, NH 03079 T 800-332-NORA www.nora.com/us

1.4. Emergency Telephone Number

Emergency Number: 800-424-9300 CHEMTREC

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Classification (GHS-US)

Acute Tox. 4 (oral) H302 Acute Tox. 4 (dermal) H312 Skin Corr. 1B H314 Eye Dam. 1 H318 Skin Sens. 1 H317 Muta. 2 H341 STOT RE 2 H373 Aquatic Chronic 2 H411 Full text of H-phrases: see section 16.

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US):







Version: 2.0



Signal Word (GHS-US): Danger

Hazard Statements (GHS-US): H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H341 - Suspected of causing genetic defects.

H373 - May cause damage to organs (liver, kidneys, nervous system, skin) through prolonged

or repeated exposure.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary Statements (GHS-US): P260 - Do not breathe vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

05/11/2015 1/11 EN (English US)

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 – Wear respiratory protection, eye protection, face shield, protective clothing, protective gloves.

P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell.

P303+P361+P353 - IF ON SKIN (or HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Name	Product Identifier	% (w/w)
Tetraethylenepentamine	(CAS No) 112-57-2	15 - 40
Fatty acids, C18-unsaturated, dimers, polymers with tall-		
oil fatty acids and triethylenetetramine	(CAS No) 68082-29-1	15 - 40
Phenol	(CAS No) 108-95-2	10 - 30
Propanol, oxybis-, dibenzoate	(CAS No) 27138-31-4	3 - 7
DETA, Diethylenetriamine	(CAS No) 111-40-0	1 - 5

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible). Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Immediately flush skin with plenty of water for at least 60 minutes. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 60 minutes. Immediately call a POISON CENTER or doctor/physician.

Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISION CENTER or doctor/physician.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: May cause an allergic skin reaction. Harmful if swallowed, in contact with skin or if inhaled. Causes severe skin burns and eye damage. Suspected of causing genetic defects. May cause damage to organs (kidney, liver, skin, nervous system) through prolonged or repeated exposure.

Inhalation: May cause respiratory irritation.

Skin Contact: Causes severe skin burns. Symptoms may include: Redness. Pain. Serious skin burns. Blisters.

Eye Contact: Causes serious eye damage. Symptoms may include: Redness. Pain. Blurred vision. Severe burns. Causes permanent damage to the cornea, iris, or conjunctiva.

Ingestion: Harmful if swallowed.

Chronic Symptoms: Suspected of causing genetic defects. May cause an allergic skin reaction. May cause damage to organs (kidney, liver, skin, nervous system) through prolonged or repeated exposure.

05/11/2015 EN (English US) 2/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Product is not flammable. Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions are unlikely to occur under normal circumstances.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. Closed containers exposed to heat may explode. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Under fire conditions this material may produce hazardous carbon dioxide (CO₂), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke. Nitrogen oxides.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing vapor, mist, or spray. Use only outdoors or in a well-ventilated area.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8, Exposure Controls and Personal Protection. For further information refer to Section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: When heated to decomposition, emits toxic fumes. Product to be handled in a closed system and under strictly controlled conditions.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

05/11/2015 EN (English US) 3/11

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s) No use is specified

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Phenol (108-95-2)		
USA ACGIH	ACGIH TWA (ppm)	5 ppm
		Skin - potential significant contribution to overall exposure
		by the cutaneous route; Not Classifiable as a Human
USA ACGIH	ACGIH chemical category	Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	19 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	5 ppm
USA OSHA	Limit value category (OSHA)	prevent or reduce skin absorption
USA NIOSH	NIOSH REL (TWA) (mg/m³)	19 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	5 ppm
USA NIOSH	NIOSH REL (ceiling) (mg/m³)	60 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (ppm)	15.6 ppm
USA IDLH	US IDLH (ppm)	250 ppm
Alberta	OEL TWA (mg/m³)	19 mg/m³
Alberta	OEL TWA (ppm)	5 ppm
British Columbia	OEL TWA (ppm)	5 ppm
Manitoba	OEL TWA (ppm)	5 ppm
New Brunswick	OEL TWA (mg/m³)	19 mg/m³
New Brunswick	OEL TWA (ppm)	5 ppm
Newfoundland & Labrador	OEL TWA (ppm)	5 ppm
Nova Scotia	OEL TWA (ppm)	5 ppm
Nunavut	OEL STEL (mg/m³)	38 mg/m³
Nunavut	OEL STEL (ppm)	10 ppm
Nunavut	OEL TWA (mg/m³)	19 mg/m³
Nunavut	OEL TWA (ppm)	5 ppm
Northwest Territories	OEL STEL (mg/m³)	38 mg/m³
Northwest Territories	OEL STEL (ppm)	10 ppm
Northwest Territories	OEL TWA (mg/m³)	19 mg/m³
Northwest Territories	OEL TWA (ppm)	5 ppm
Ontario	OEL TWA (ppm)	5 ppm
Prince Edward Island	OEL TWA (ppm)	5 ppm
Québec	VEMP (mg/m³)	19 mg/m³
Québec	VEMP (ppm)	5 ppm
Saskatchewan	OEL STEL (ppm)	7.5 ppm
Saskatchewan	OEL TWA (ppm)	5 ppm
Yukon	OEL STEL (mg/m³)	38 mg/m ³

05/11/2015 EN (English US) 4/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Yukon	OEL STEL (ppm)	10 ppm
Yukon	OEL TWA (mg/m³)	19 mg/m³
Yukon	OEL TWA (ppm)	5 ppm

8.2. Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure, but are not required. Product to be handled under strictly controlled conditions. Ensure all national/local regulations are observed. Gas detectors should be used when toxic gases may be released. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits. Personal Protective Equipment: Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection. Face shield.











Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves. Eye Protection: Chemical safety goggles and face shield. Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Environmental Exposure Controls: Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink or smoke during use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Liquid **Physical State:** Thick liquid Appearance: Armine odor Odor: Not available Odor Threshold: Not available :Ha Not available **Evaporation Rate: Melting Point:** Not available Freezing Point: 32 °F

Boiling Point: 356 °F (≈180 °C)

Flash Point: > 200 °F (93 °C) (Tag Closed Cup)

Not available Auto-ignition Temperature: **Decomposition Temperature:** Not available Not available Flammability (solid, gas): Not available Lower Flammable Limit: Not available Upper Flammable Limit: Not available Vapor Pressure: Not available Relative Vapor Density at 20 °C: Not available Relative Density:

Specific Gravity: 1.0

Solubility: Not available Partition Coefficient: N-Octanol/Water: Not available Viscosity: 400 - 900 cps

Explosion Data – Sensitivity to Mechanical Impact: Not expected to present an explosion hazard due to mechanical impact.

05/11/2015 EN (English US) 5/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Explosion Data – Sensitivity to Static Discharge:

Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

- **10.1. Reactivity** Hazardous reactions are unlikely to occur under normal circumstances.
- **10.2. Chemical Stability** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions Not available
- **10.4. Conditions to Avoid** Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.
- **10.5. Incompatible Materials** Strong acids. Strong bases. Strong oxidizers.
- **10.6. Hazardous Decomposition Products** Under fire conditions this material may produce hazardous carbon dioxide (CO₂), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke. Nitrogen oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity: Oral - Harmful if swallowed. Dermal - Harmful in contact with skin. Inhalation - dust, mist - Harmful if inhaled. LD50 and LC50 Data:

ATE US (oral)	532.01 mg/kg body weight
ATE US (dermal)	1,067.77 mg/kg body weight
ATE US (dust, mist)	1.46 mg/l/4h

Skin Corrosion/Irritation: Causes skin burns and eye damage. Serious Eye Damage/Irritation: Causes serious eye damage.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Suspected of causing genetic defects.

Teratogenicity: Not available Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): May cause damage to organs (liver, kidneys, nervous system, Skin) through

prolonged or repeated exposure. Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause respiratory irritation.

Symptoms/Injuries After Skin Contact: Causes severe skin burns. Symptoms may include: Redness. Pain. Serious skin burns. Blisters. Symptoms/Injuries After Eye Contact: Causes serious eye damage. Symptoms may include: Redness. Pain. Blurred vision. Severe

burns. Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: Harmful if swallowed.

Chronic Symptoms: Suspected of causing genetic defects. May cause an allergic skin reaction. May cause damage to organs (kidney, liver, skin, nervous system) through prolonged or repeated exposure.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

ED30 and EC30 Data.	
Phenol (108-95-2)	
LD50 Oral Rat	340 mg/kg
LD50 Dermal Rabbit	630 mg/kg
LC50 Inhalation Rat	0.316 mg/l/4h (reported as 316 mg/m³/4h)
ATE US (gases)	700.00 ppmV/4h
Diethylenetriamine (111-40-0)	
LD50 Oral Rat	1080 mg/kg

05/11/2015 EN (English US) 6/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

LD50 Dermal Rabbit	672 mg/kg	
LC50 Inhalation Rat	0.3 mg/l/4h	
Tetraethylenepentamine (112-57-2)		
LD50 Oral Rat	2100 mg/kg	
LD50 Dermal Rabbit	660 - 1260 mg/kg	
Fatty acids, C18-unsaturated, dimers, polyr	mers with tall-oil fatty acids and triethylenetetramine (68082-29-1)	
LD50 Oral Rat	> 2000 mg/kg	
LD50 Dermal Rat	> 2000 mg/kg	
Stoddard solvent (8052-41-3)		
LD50 Oral Rat	> 5 g/kg Behavioural somnolence	
LD50 Dermal Rabbit	> 3 mg/kg	
Phenol (108-95-2)		
IARC Group	3	
National Toxicology Program (NTP) Status	Twelfth Report - Items under consideration	

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology – General: Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Phenol (108-95-2)	
LC50 Fish 1	11.9 - 50.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	4.24 - 10.7 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC 50 Fish 2	20.5 - 25.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	10.2 - 15.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Diethylenetriamine (111-40-0)	
LC50 Fish 1	248 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])
EC50 Daphnia 1	16 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	1014 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static])
Tetraethylenepentamine (112-	57-2)
LC50 Fish 1	420 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])
EC50 Daphnia 1	24.1 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and Degradability Not available

12.3. Bioaccumulative Potential

Phenol (108-95-2)	
BCF Fish 1	(no significant bioaccumulation)
Log Pow	1.47
Diethylenetriamine (111-40-0)	
BCF Fish 1	0.3 - 1.7
Log Pow	-1.3
Tetraethylenepentamine (112-57-2)	
BCF Fish 1	(no bioaccumulation expected)
Log Pow	<1

05/11/2015 EN (English US) 7/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

12.4. Mobility in Soil Not available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Sewage Disposal Recommendations: This material is hazardous to the aquatic environment. Keep out of sewers and waterways. Do not empty into drains; dispose of this material and its container in a safe way.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT

Proper Shipping Name: TETRAETHYLENEPENTAMINESolution

Hazard Class: 8

Identification Number: UN2320

Label Codes: 8
Packing Group: III

Marine Pollutant: Marine pollutant

ERG Number: 153

14.2. In Accordance with IMDG

Proper Shipping Name: TETRAETHYLENEPENTAMINESolution

Hazard Class: 8

Identification Number: UN2320

Label Codes: 8
Packing Group: III
EmS-No. (Fire): F-A
EmS-No. (Spillage): S-B

Marine Pollutant: Marine pollutant

14.3. In Accordance with IATA

Proper Shipping Name: TETRAETHYLENEPENTAMINESolution

Hazard Class: 8

Identification Number: UN2320

Label Codes: 8
Packing Group: III
ERG Code (IATA): 8L

14.4. In Accordance with TDG

Proper Shipping Name: TETRAETHYLENEPENTAMINESolution

Hazard Class: 8

Identification Number: UN2320

Label Codes: 8
Packing Group: III

Marine Pollutant (TDG): Marine pollutant







05/11/2015 EN (English US) 8/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

13.1. 03 i cuciui negululions		
CARA Section 211/212 Horard Classes	Immediate (acute) health hazard	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard	
Phenol (108-95-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Listed on the United States SARA Section 302		
Listed on United States SARA Section 313		
	T - T - indicates a substance that is the subject of a Section 4 test	
EPA TSCA Regulatory Flag	rule under TSCA.	
SARA Section 302 Threshold Planning Quantity (TPQ)	≤ 10000	
SARA Section 313 - Emission Reporting	1.0 %	
Diethylenetriamine (111-40-0)		
Listed on the United States TSCA (Toxic Substances Control	Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.	
Tetraethylenepentamine (112-57-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Fatty acids, C18-unsaturated, dimers, polymers with tall-oil fatty acids and triethylenetetramine (68082-29-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Propanol, oxybis-, dibenzoate (27138-31-4)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		

15.2. US State Regulations

Phenol	(108-95-2)
1 1101101	100 33 21

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Diethylenetriamine (111-40-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Tetraethylenepentamine (112-57-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

05/11/2015 EN (English US) 9/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

15.3. Canadian Regulations

nora® 310 B	
	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
WHMIS Classification	Class E - Corrosive Material



Phenol (108-95-2)	
Listed on the Canadian DSL (Dom	nestic Substances List)
Listed on the Canadian IDL (Ingre	dient Disclosure List)
IDL Concentration 1 %	
	Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class E - Corrosive Material
	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Diethylenetriamine (111-40-0	
Listed on the Canadian DSL (D	Oomestic Substances List)
Listed on the Canadian IDL (Ir	gredient Disclosure List)
IDL Concentration 0.1 %	
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
WHMIS Classification	Class E - Corrosive Material
Tetraethylenepentamine (112	2-57-2)
Listed on the Canadian DSL (C	Oomestic Substances List)
Listed on the Canadian IDL (In	gredient Disclosure List)
IDL Concentration 1 %	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class E - Corrosive Material
	dimers, polymers with tall-oil fatty acids and triethylenetetramine (68082-29-1)
Listed on the Canadian DSL (D	
NAU IN AIG Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
WHMIS Classification	Class E – Corrosive Material
Propanol, oxybis-, dibenzoate	
Listed on the Canadian DSL (D	,
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date: 05/11/2015

This document has been prepared in accordance with the SDS requirements of the OSHA

Other Information: Hazard Communication Standard 29 CFR 1910.1200.

05/11/2015 EN (English US) 10/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

GHS Full Text Phrases:

H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H332	Harmful if inhaled
H341	Suspected of causing genetic defects
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

Party Responsible for the Preparation of This Document

nora systems, Inc.

T 800-332-NORA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2

05/11/2015 EN (English US) 11/11