







1.	<b>Initial cleaning after installation</b>	 <p>Remove dry, loose dirt with a suitable procedure.</p>	 <p>Make sure you spray a suitable cleaning agent (see Cleaning and polishing agents table) using a red pad*.</p>
2.	<b>Routine cleaning/ polishing</b>	 <p>Damp-wipe with a spray-dampened or prepared cleaning cloth (gauze cloths).</p>	 <p>If wipe polish products (see Cleaning and polishing agents table) are used, polishing** as needed at periodic intervals using a suitable white polishing pad* is recommended.</p>
3.	<b>Intermediate cleaning</b>	 <p>Remove dry, loose dirt with a suitable procedure.</p>	 <p>Make sure you spray a suitable cleaning agent (see Cleaning and polishing agents table) using a red pad*.</p>

**General notes:**

- As coatings require regular and cost-intensive basic cleaning and renewal, nora systems GmbH recommends that norament® rubber floor coverings, which are leakproof and have sealed surfaces, not be coated.
- Please observe the instructions in the product and safety data sheets of the cleaning & polishing agents used.
- \* Suitable pads: 3 M, etc.
- \*\* Use single-disk polishing machine with rotation speeds between 300 - 800 rpm (polishing brush) or 1000 - 1500 rpm (polishing pad).  
Alternatively, you can also use a high speed machine with rotation speeds between 300 - 800 rpm (polishing pad).

Should you have any further questions please contact nora Technical Service, [www.nora.com](http://www.nora.com)  
More detailed explanations of the cleaning procedures can be found in our document "Cleaning Definitions".

# Cleaning recommendation norament® 975 LL

## Cleaning and polishing agents

The cleaning and polishing agents listed in the table are **recommendations by cleaning agent manufacturers in the German market**. Depending on the premises, it may be useful to use **products and processes that differ from the standard, but according to the cleaning agent manufacturer's recommendation**. Please observe **the product-specific manufacturer's instructions!** Of course, you can also use suitable cleaning agents from non-listed cleaning agent manufacturers according to their recommendations. nora recommends to observe the following list, as from our experience, best results are achieved with these cleaning agents.

Companies	Initial/intermediate cleaning	Routine cleaning/polishing
Diversey GmbH 68219 Mannheim Tel. +49 (0)621 / 8757-0	Taski Combi 800 ml to 8 l water	Taski tensol, 40 ml – 80 ml to 8 l water If necessary, change to Taski 300, 80 ml to 8 l water
Dr. Schnell Chemie GmbH 80807 München Tel. +49 (0)89/350 608-0	FLOORTOP 800 ml to 8 l water	FLOORTOP, 40 ml to 8 l water If necessary, change to SCHIROCCO CLEAN, 40 ml – 80 ml to 8 l water
Ecolab Deutschland GmbH 40789 Monheim am Rhein Tel. +49 (0)2173/599-0	Maxx Indur 2 800 ml to 8 l water	Maxx Indur 2, 40 ml – 80 ml to 8 l water If necessary, change to Maxx Magic 2, 40 ml to 8 l water
Johannes Kiehl KG 85235 Odelzhausen Tel. +49 (0)8134/9305-0	Procur concentrate 200 ml to 8 l water	Procur concentrate, 25 ml to 8 l water If necessary, change to Veriprop, 40 ml to 8 l water (1 dosage)
Tana-Chemie GmbH 55120 Mainz Tel. +49 (0)6131 / 964-03	TAWIP original 800 ml to 8 l water	TAWIP original, 40 ml – 80 ml to 8 l water If necessary, change to TANET extreme, 40 ml – 60 ml to 8 l water
KLEEN Purgatis GmbH 32120 Hiddenhausen Tel. +49 (0)5223/9970-40	PREMIUM No 4 800 ml to 8 l water	PREMIUM No 4, 40 ml to 8 l water If necessary, change to Blue Star Ocean, 40 ml to 8 l water
Dreiturm GmbH 36396 Steinau a. d. Str. Tel. +49 (0)6663/970-0	GOLDREIF Klarwischpflege 200 ml to 8 l water	GOLDREIF Klarwischpflege, 40 ml to 8 l water If necessary, change to MULTINETZER, 40 ml to 8 l water
Dr. Schutz GmbH 53175 Bonn Tel. +49 (0)228/95352-0	Floor cleaner R1000 800 ml to 8 l water	Floor cleaner R1000, 40 ml to 8 l water If necessary, change to PU cleaner, 40 ml to 8 l water
Buzil-Werk Wagner GmbH & Co. KG 87700 Memmingen Tel. +49 (0)8331 / 930-6	S 780 Corridor® Daily 800 ml to 8 l water	S 780 Corridor® Daily, 40 ml to 8 l water If necessary, change to S766 Corridor PUR Clean, 40 ml to 8 l water